

# STS VJ-628D

## Direct to Film Printer



<b>Print Method</b>	Drop-On Demand, Piezo Drive
<b># of nozzles / # of heads</b>	(180 x 8 rows) / 1 head
<b>Ink type</b>	DTF
<b>Variable dot</b>	Yes
<b>Minimum droplet size</b>	3.5 pl
<b>Print modes</b>	720/540/360 dpi 12 modes +
<b>Color options</b>	CMYK + 2W + 2 Cleaning
<b>Maximum resolution</b>	1440 dpi
<b>Head height</b>	Low: 12mm / High 2.5mm
<b>Maximum media width</b>	24.8 inches
<b>Maximum print width</b>	24.4 inches
<b>Heating system</b>	Pre / Post
<b>Media roll diameter / Core</b>	6' maximum / Core 3" or 2"
<b>Stand</b>	Optional
<b>Media Auto Cut</b>	Standard
<b>RIP software</b>	SAI/ White RIP STS – DTF
<b>Power requirements</b>	110/220 Volt
<b>Operating temperature</b>	68°F – 75°F
<b>Operating humidity range</b>	45% -55%
<b>Dimensions (printer) WxDxH</b>	47" x 17" x 14"
<b>Dimensions (printer with stand)</b>	47" x 23" x 46"
<b>Weight (printer)</b>	Printer 70 lbs / Stand 19 lbs
<b>Weight (shipping info)</b>	Call for quote
<b>Limited warranty</b>	1 Year