

Technical Specifications

Standard Features

- Manual, Swing Away & Pull-out design
- Self-diagnostics help with troubleshooting and maintenance.
- Heating Area: 16" x 20"
- Lower Platen Threadability[™] makes it easy to load & un-load garments
- Easy-to-install interchangeable platens Quick Change lower platens
- Multiple time settings.
- Auto on/off setting & Energy-saving 4 hour sleep mode.
- Production cycle counter—Available in (8) languages.
- Upper Platen: 3/4" thick Coated Non-Stick
- Customizable for: F° (Fahrenheit) or C° (Celsius)
- Live digital time, temperature, and pressure readout.
- Temperature range: 32°F 430°F
- Approved: UL/ULC/CE/RoHS compliant
- Must have designated circuit breaker
- Standard Electrical: 120 volts /15 amps /1800 watts
- Special Custom: 240 volts /15 amps / 3500 watts
- · Cast-aluminum frame.

Press Size: 16x20

• Actual Weight: 137 lbs

Shipping Weight: 150 lbs

• Dimensions: 32" x 18" x 20"

Shipping Dimensions: 37" x 25" x 24"

Hotronix Premier Warranty

- Lifetime Warranty on Heating Element
- 5 years on Framework
- 2 years on Circuit board
- 1 year PARTS/LABOR



